



SPECIFICATIONS & PARTS

Zebra® ZVac™ II Sump Assistant

V2 Series - Technical Specifications

All Models	
Flow Rate, intake:	40 gpm (151 lpm)
Flow Rate, Discharge:	40 gpm (151 lpm)
Material, main body:	Powder-coated steel
Liquid Container:	48 gallons (182 l)
Chip Container:	8 gallons (30 l) w/ .08" (2mm) pore size, and rubber gasket, 23" dia. x 6" high
Inlet Size:	2" (51mm) diameter
Intake Hose:	2" (51mm) diameter, 15' (5m) long
Discharge Handle:	Cast aluminum w/lock lever
Required Discharge Level:	1 gallon (for priming of discharge pump only)
Drain Valve:	2" (51mm) stainless steel full port ball valve and cast stainless housing
Cord Length:	30' (10m) w/cord wrap mechanism
Casters:	6" (15.2cm) diameter, positive engagement locking mechanism, (2) 360° swivel
Lid/Primary Access:	10 gauge steel w/wide rim for tight seal, 23" diameter
Control Panel:	Easy to understand controls
Dimensions:	42 x 26.5 x 59" (107 x 67.3 x 150 cm)
Standard Tools:	Hose cuffs (2), curved intake tube, and rubber cone w/angled edge

Models	V2-110.1	V2-220.1	V2-220.3	V2-440.3
Phases:	1	1	3	3
Voltage:	110/120	220/240	220/240	440/480
Watts:	1460	1460	2550	2550
Amps, motor:	14.1/6.1	14.1/6.1	10.9/6.0	10.9/6.0
Amps, pump:	5.0/2.7	5.0/2.7	2.3/1.15	2.3/1.15
Horsepower, min.:	1.8	1.8	3	3
CFM:	105	105	219	219
Waterlift, inches:	131	131	145	145
Weight, pounds:	265	265	325	325

V2 Series - Replacement Parts & Accessories

VXSSB	Steel Filter Container, 500µ
VXRCA	Rubber Cone Attachment, 6" long w/angled edge
VXCuff	Hose cuff, 2" ID (2)
VXCSI	Curved Intake Tube, 24" long
VXIHose-2	Intake Hose, 2" (50mm) ID, copper spiral wound, sold per meter
VXDHose-1	Discharge Hose, 1" (25mm) ID, steel spiral wound, sold per meter
VXF.2-100	Filter Bag Insert, 100µ
VXF.2-050	Filter Bag Insert, 50µ
VXOMF	Oil Mist Filter
VXCSW	Continuous Suction Wand, 36" long, w/breather
VXEW-60	Extension Wand, 60" long, steel
VXMCA	Metal Crevice Attachment, 20" long
VXMCBA-N	Metal Crevice Attachment w/Nylon Bristles, 12" long
VXMCBA-S	Metal Crevice Attachment w/Steel Bristles, 12" long
VXBA-3	Brush Attachment, 3" round
VXFRNA	Flat Rubber Nozzle, 5" long
VXTCA	Tapered Cone Attachment, 12" long, rubber
VXWand	Double-Curved Floor Wand, 54" long, aluminum
VXWFN	Wheeled Floor Squeegee/Brush Attachment, 16" wide, height adjustable
VXAC	Accessory Coupler (required for some non-standard accessories)



Zebra Skimmers Corporation
 PO Box 833 Chagrin Falls, OH 44022
www.ZebraSkimmers.com
www.CoolantMaintenance.com
 Toll Free 888-249-4855
 Phone: 440.349.0141
 Fax: 440.349.1211

© May 2008 Zebra Skimmers Corp. All rights reserved.

Contact your distributor
 for more information